

2018 CDL Roth Sugar Bush Spring Sale

CDL ROTH SUGAR BUSH

List Price = \$2,600.00

List Price = \$6.000.00

Featured Items of the Week NEW HOBBY Reverse Osmosis



List Price = \$4.950.00

81050 HOBBY RO - 50 GPH HOBBY RO 1X 0.75 HP SUPPLY-PRESSURE PUMP.

INCLUDED: 1X CARTRIDGE HOUSING. 1X 4" MEMBRANE. 1X INLET STRAINER.

AVAILABLE: STORAGE CANISTER. WASHING TANK.

NOTE: SUPPLY, CONCENTRATE AND PERMEATE HOSE ARE 7' LONG. ELECTRICAL SUPPLY WIRE IS 15' LONG.

TOTAL FLOW: 50 GPH

List Price = \$10,950.00

CONCENTRATE FLOW: 25 GPH

TOTAL ELECTRIC CONSUMPTION: 10.5 AMP AT 120 VOLTS SINGLE PHASE.

81125V HOBBY RO - 100 GPH

1X 0.75 HP SUPPLY-PRESSURE PUMP. 1X 0.5 HP RECIRCULATION PUMP.

INCLUDED:

1X CONCENTRATE FLOWMETER.

1X PERMEATE FLOWMETER.

1X CARTRIDGE HOUSING

1X 4" MEMBRANE.

1X INLET STRAINER.

AVAILABLE: STORAGE CANISTER. WASHING TANK.

NOTE: SUPPLY, CONCENTRATE AND PERMEATE HOSE ARE 7' LONG.

ELECTRICAL SUPPLY WIRE IS 15' LONG.

TOTAL FLOW: 100 GPH

CONCENTRATE FLOW: 50 GPH FROM 4 BRIX TO 8 BRIX

TOTAL ELECTRIC CONSUMPTION: 16 AMP AT 120 VOLTS SINGLE PHASE.

81250V HOBBY RO 200 GPH

1X 0.75 HP SUPPLY-PRESSURE PUMP. 1X 0.5 HP RECIRCULATION PUMP.

INCLUDED:

1X CONCENTRATE FLOWMETER.

1X PERMEATE FLOWMETER.

1X CARTRIDGE HOUSING.

2X 4" MEMBRANE. 1X INLET STRAINER

IX INCE I OTTO MINER.

AVAILABLE: STORAGE CANISTER. WASHING TANK.

NOTE: SUPPLY, CONCENTRATE AND PERMEATE HOSE ARE 7' LONG.

ELECTRICAL SUPPLY WIRE IS 15' LONG.

TOTAL FLOW: 200 GPH

CONCENTRATE FLOW: 100 GPH FROM 4 BRIX TO 8 BRIX

TOTAL ELECTRIC CONSUMPTION : 16 AMP AT 120 VOLTS SINGLE PHASE.

816005E RO CLASSIC 600 GPH

SUPPLY PUMP: 1X 1.0 HP 20 GPM SINGLE STAGE. HIGH PRESSURE PUMP: 1X 5.0 HP 12 GPM MULTI-STAGE. RECIRCULATION PUMP: 1X 1.0 HP 85 GPM SINGLE STAGE.

FILTRATION UNIT ELECTRICAL PLUGS: 1X 1.0 HP.

CONCENTRATE FLOWMETER: 1X 0-10 GPM WITH SAMPLE VALVE

CONCENTRATE CONTROL AND READING: MANUAL

PRE-FILTRATION: 1X SINGLE 20" FILTER HOUSING ON MAIN UNIT.

WASHING TANK: 1X 25 GALLONS ON MAIN UNIT.

HIGH PRESSURE HOSES: 1X 3/4" X 60". 1X 5/8" X 60".

MEMBRANE POSTS: 1X STANDARD 8" SUBMERSIBLE.

MEMBRANES: 1X CDL MRO MAX 8" X 40"

MEMBRANE STORAGE CANISTERS: 1X 8" 8" MEMBRANE POSTS CONFIGURATION: VERTICAL INDIVIDUAL

HIGH FLOW RINSE: N/A.

PERMEATE FLOWMETERS: 1X 0-10 GPM ON MAIN UNIT.

AVAILABLE OPTIONS: INTEGRATED RINSE.

CONTINUOUS BRIX READER

CONTINUOUS BRIX READER WITH MODULATING VALVE.

INSTALLATION BY A CDL TECHNICIAN.

NOMINAL MAIN UNIT CAPACITY: FLOW AT 350 PSI : 660 GPH FLOW AT 400 PSI : 600 GPH FLOW AT 450 PSI : 540 GPH

NOMINAL FILTRATION UNIT CAPACITY AT 45°F AND

100% MEMBRANES EFFICIENCY COMBINE WITH NOMINAL MAIN UNIT CAPACITY: 8° BRIX: 595 GPH 10° BRIX: 570 GPH 12° BRIX: 560 GPH

TOTAL POWER CONSUMPTION: 38 AMPERES AT 240 VOLTS SINGLE PHASE.

POWER SUPPLY BLOCK: 1X 175 AMPERES 120/240 VOLTS

MINIMAL REQUIRED PERMEATE QUANTITY FOR A WASHING OPERATION: 600 GALLONS. 2 YEARS PARTS AND LABOR LIMITED WARRANTY.



Please Call Us At 715-289-3820

With Questions & For More Info on these and ALL the other items on sale now!